

Eugene Location

Phone: 5413425317
29512 Airport Rd
Eugene, OR
Email: info@cascadetruckbody.com



B&W TS20037B Tow & Stow

Stock#: 274201 Year: 2022 Manufacturer: B and W Trailer Hitches

Axle Capacity: 0.00

URL: <https://cascadetruckbody.com/b-w-ts20037b-tow-stow-6oSn.html>

Price	\$324.00
-------	----------

Description

B&W TS20037B Tow & Stow

B and W Trailer Hitch Ball Mount - BWTS20037B
Adjustable Ball Mount
Fits 2-1/2 Inch Hitch
Drop - 5 Inch
Rise - 4-1/2 Inch
2 Inch Ball
2-5/16 Inch Ball
Two Balls
Class V
14500 lbs GTW
B and W
Steel Shank - Matte Black
Steel Ball
Stow the ball and mounting platform on this double-ball ball mount beneath your hitch for a sleek look when you are done towing. Tow up to 7,500 lbs with the 2" ball or 14,500 lbs with the 2-5/16" ball.
Features:
Ball mount with built-in hitch balls lets you hook up your trailer to your tow vehicle
Shank slides into hitch receiver
Ball provides connection point for trailer coupler
Stowable design lets you store ball and mounting platform underneath your vehicle
Remove pins holding ball mount platform in place on shank
Flip platform underneath the hitch
Reinsert pins and clips to secure ball mount platform for travel
Adjustable height lets you tow trailers of different heights with the same vehicle

Slide ball mount up or down along shank and secure in place with included pins and clips
Anti-theft design ensures ball mount platform can't be removed when Tow & Stow is installed in hitch
No additional locks required to prevent platform and balls from being removed
2 Different-size hitch balls let you tow trailers with different coupler sizes
To switch ball, simply remove pin, rotate balls, and reinsert pin
Dual-process chrome plating on balls provides excellent rust resistance
Black powder coated shank is corrosion resistant
Stainless steel pins create sturdy, rust-resistant connections
Durable steel construction with high yield tubing offers superior strength
Hitch pin and clip or hitch lock sold separately
Made in the USA

Specs:

Application: 2-1/2" x 2-1/2" trailer hitch receivers
Gross towing weight:
When used with 2" ball: 7,500 lbs
When used with 2-5/16" ball: 14,500 lbs
Distance from center of hitch pin hole to center of hitch ball:
Hitch pin hole closest to ball: 9-1/4"
Hitch pin hole farthest from ball: 10-3/8"
Distance from center of hitch pin hole to pin hole in mounting block:
Pin hole closest to mounting block: 3-3/4"
Pin hole farthest from mounting block: 4-7/8"
Maximum drop: 5"
Maximum rise: 4-1/2"
Incremental height adjustment: 1"
Minimum clearance: 11" from ground to lowest point on Tow & Stow hitch
Limited lifetime warranty

Note:

Requires a minimum of eleven inches of clearance between the ground and the lowest part of the hitch
Without adequate ground clearance, the hitch may hit the ground or other objects such as steep driveways or curbs
Striking any obstacle may cause damage to the hitch that could affect its integrity
The B&W Tow & Stow adjustable ball mount lets you tow a variety of trailers with different tongue heights. Having both a 2" ball and a 2-5/16" ball allows for even more versatility, making this the ultimate go-to ball mount if you own multiple trailers.

Easily Adjusts and Stows

To switch the hitch ball, simply remove the pin holding the balls in place and rotate the entire block that the balls are mounted on until the ball you want to use is on top. Then replace the pin to secure the block in place.
Adjusting the height of the ball is just as easy. Remove the pins holding the ball mount platform in place and slide the platform up or down along the shank to the desired position. Once you have found the correct height, reinsert the pins and replace the clips.
When you're not towing, you can flip the ball mount platform around and stow it beneath your hitch so that you won't bang your shins. Just remove the pins to slide the ball platform down along the channel and up the back side so that the hitch balls face towards your vehicle. Then replace the pins.

Built-In Anti-Theft System

The Tow & Stow ball mount features a channel that runs along both sides of the shank. This channel not only allows you to slide the ball mount platform up and down to adjust the ball height, but it also prevents removal of the platform when the ball mount is installed, which will help prevent theft of your trailer.
A slot is cut into the adjustment channel near the top of the shank. To remove the ball mount platform from the shank you will need to remove the entire ball mount from your hitch. Then remove the pins that hold the platform in place. Flip the platform around to the stowed position on the rear of the shank, and then slide it up until the center pin lines up with the slot in the shank. Pull the platform out towards the rear of the shank until the pin pops out of the adjustment channel.

When the Tow & Stow is secured in your hitch receiver, you will not be able to remove the ball mount platform. This is because the slot in the shank is positioned in such a way that the collar on your hitch will block the pin on the platform from being able to leave the channel. Even if the pins holding the ball mount platform in place are removed, the platform will still be confined to this channel. So, as long as a hitch lock is used to secure the entire ball mount in your hitch receiver, and a coupler lock is used to prevent your trailer's coupler from being disengaged from the ball, your trailer will

be secure.

****PLEASE NOTE:**

Trailer models listed on this web site does not guarantee availability. Trailer Inventory can move FAST! Some pictures can be from several styles and sizes of trailers with or without extra options. Please Contact our Stores for current availability, pricing and factory lead times.

Cascade Truck Body and Trailer Sales

The Best Brands, The Best Value , and The Best Service.

Cascade Truck Body and Trailer Sales carries the Best Brands of enclosed trailers, utility trailers, dump trailers, flatbeds and equipment trailers.

We stock Race Trailers fully equipped and ready for the track. If we don't have the exact trailer, you are looking for in stock, Cascade can assist you in building a competitively priced customized trailer while maintaining the highest quality of products. Call our sales staff for a friendly no pressure quote.

Cascade Truck Body and Trailer Sales is an authorized factory dealer for Alcom Trailers, ATC Trailers, Aluma Trailers, Big Tex, Cargo Mate, Eagle Trailers, H&H Trailers, Futura Trailers, Performax Custom Trailers, Stehl Tow Dollies, Triple L Trailers, and Wells Cargo

We have a Full-Service Fabrication Shop at our Eugene Location that is available for all your work truck or trailer needs. No Repair or Install is too small or too big

EUGENE STORE

29512 Airport Road

Eugene, OR 97402

Open: Monday-Friday 8am-5pm Saturday 9am- 3pm

Call Direct (541) 342-5317

TUMALO STORE

64601 Bailey Road

Bend, OR 97703

Open: Monday-Friday 8am-5pm Saturday Closed

Call Direct (541) 389-9849

SALEM STORE

Cascade Truck Body and Trailer Sales

4835 Portland Road NE

Salem, OR 97305

Open: Monday-Friday 8am-5pm Saturday Closed

Call Direct (503) 385-1447

REDMOND STORE

Cascade Truck Body and Trailer Sales

3920 N. Hwy 97

Redmond, OR 97756

Call Direct (541) 389-9849

Disclaimer

MSRP Prices Exclude State and Local Taxes and Registration Fee's

Personal Checks are No-Longer Accepted

Credit Card Processing of 3% will be applied on all credit and debit card purchases over \$1500.

All prices, specifications and measurements are subject to change without notice.

Trailer dimensions, weights, and measurements will vary due to manufacturing and production changes. Please verify actual measurements of any unit prior to purchase.